

Provisorische Bahndaten

Kat.	Distanz km	Steigung m	Anzahl Posten	Start
H10	2.5	40	10	2
H12	2.7	80	10	2
H14	3.1	150	12	2
H16	3.9	170	13	1
H18	4.1	190	12	1
H20	5.2	250	17	1
HE	5.2	250	17	1
HAL	4.2	180	15	1
HAM	3.2	140	11	1
HAK	2.5	120	10	1
HB	2.6	110	9	2
H35	4.1	165	13	1
H40	4.1	195	13	1
H45	4.2	170	14	1
H50	4.1	160	12	1
H55	4.2	150	13	1
H60	3.7	160	12	1
H65	3.4	130	12	1
H70	2.9	120	10	2
H75	2.6	120	9	2
H80	2.3	70	9	2
H85	2.0	40	8	2

Kat.	Distanz km	Steigung m	Anzahl Posten	Start
D10	2.3	40	10	2
D12	2.7	50	11	2
D14	2.7	120	11	2
D16	3.1	140	12	1
D18	3.0	150	10	1
D20	4.4	210	13	1
DE	4.4	210	13	1
DAL	3.6	150	11	1
DAM	2.7	115	11	1
DAK	2.2	60	8	1
DB	2.3	90	9	2
D35	3.1	110	11	1
D40	3.4	125	13	1
D45	3.3	125	12	1
D50	3.4	115	10	1
D55	3.1	110	10	1
D60	3.0	110	10	1
D65	2.6	90	10	1
D70	2.4	70	9	2
D75	2.0	50	8	2
D80	1.9	40	8	2

OS	2.3	40	9	3
OK	2.3	60	8	3
OM	2.6	110	10	3
OL	3.4	140	12	3
FAM	2.2	50	8	3

Massstab
1:10'000
1:7'500

