

MOM 2025: Streckendaten

Kat.	Distanz km	Steigung m	Anzahl Posten	Start
D10	2.3	45	10	2
D12	2.7	65	10	2
D14	2.7	125	11	2
D16	3.1	160	11	1
D18	3.0	170	10	1
D20	4.2	210	13	1
DE	4.2	210	13	1
DAL	3.6	165	11	1
DAM	2.8	115	11	1
DAK	2.2	60	8	1
DB	2.4	90	9	2
D35	3.2	110	11	1
D40	3.5	135	13	1
D45	3.5	140	13	1
D50	3.4	120	10	1
D55	3.1	115	10	1
D60	3.0	100	10	1
D65	2.6	90	10	1
D70	2.4	85	9	2
D75	2.0	50	8	2
D80	1.9	50	8	2

Kat.	Distanz km	Steigung m	Anzahl Posten	Start
H10	2.5	65	10	2
H12	2.7	75	10	2
H14	3.1	150	12	2
H16	3.9	180	13	1
H18	4.1	210	12	1
H20	5.2	250	17	1
HE	5.2	250	17	1
HAL	4.4	200	14	1
HAM	3.2	145	11	1
HAK	2.6	120	10	1
HB	2.6	110	9	2
H35	4.1	200	13	1
H40	4.1	210	13	1
H45	4.4	160	14	1
H50	4.4	175	13	1
H55	4.1	170	14	1
H60	3.7	180	12	1
H65	3.4	135	13	1
H70	2.9	125	10	2
H75	2.6	120	9	2
H80	2.3	60	9	2
H85	2.1	50	8	2

OS	2.3	50	9	3
OK	2.3	60	8	3
OM	2.6	110	10	3
OL	3.4	130	12	3
FAM	2.4	60	9	3

Massstab
1:10'000
1:7'500

